

PRODUCT DATA

Turntable System — Type 9640

Turntable System Type 9640 consists of Controllable Turntable Type 5960, Turntable Controller Type 5997 and Remote Control WB 1254. The Turntable System is designed to rotate a test object, such as a loudspeaker, microphone, or hydrophone, for measurement of directional response. Used in combination with a personal computer, Type 9640 becomes part of a system capable of automatically recording the directional characteristics of many different test objects.



USES

- Controlling test-object (e.g., loudspeaker, microphone, hydrophone) orientation during:
 - Directional response measurements
 - Sound power measurements
 - Directional noise radiation measurements

FEATURES

- Rotation of up to 100 kg load, supported or suspended

- Continuous, relative or absolute rotation
- Controlled from turntable controller, remote control unit or PC over IEEE-488 interface
- Adjustable turntable speed and acceleration
- Connection of test object power supply and signal through slip ring
- Front panel read-out of mode and current test-object position

Applications

Type 9640 can be used to measure directivity by means of frequency-response test methods. The test object can be accurately rotated using the Turntable System so that it is located at the desired angle to a measurement microphone. The response of the test object can then be obtained for any direction using PULSE Directivity and Polar Plot BZ 5551.

Controlling the Turntable

Turntable Controller Type 5997 offers three modes of operation (Turn_Rel, Turn_Abs and Cont.) and three commands Set 0°, Acc. and Max_360. Turn_Rel and Turn_Abs allow a relative or absolute turn (specified in degrees) to be made. When a polar plot of a single frequency is required, the CONT mode is to be selected as it rotates the turntable continuously at a constant speed.

As test objects have different inertia, the acceleration and deceleration in the start and stop phases can be controlled

by using the command ACC. The acceleration of the turntable can be adjusted to accommodate different test object masses, up to 100 kg.

The Set 0° command is used to set the zero degree mark that will be the reference for a given test. In order to prevent cable wrapping, the MAX_360 command limits the turns between 0° and 360°. Alternatively, the cable can be fed through the slip ring on the turntable, allowing an unlimited number of rotations.



Remote Control WB 1254 offers 5 commands for controlling Turntable Type 5960 via a 15 m cable. The “<” and “>” keys are used to turn the test object clockwise and anticlockwise, respectively. When the test object has been positioned at the starting point, the zero degree mark can be set by pressing Set 0°. The mode of operation can be chosen at the front panel of Turntable Controller Type 5997. The turntable can then be started or stopped by using the Start and Stop keys.

Connections to the Test Object

Two types of connection can be made from the base plate of the turntable, through slip rings, to the test object on the table plate. One supplies power to the test object while

the other, a screened coaxial connection, carries signals to and from the test object. The connections are heavily screened from each other, making spurious signals negligible under normal conditions.

Compliance with Standards

 	CE-mark indicates compliance with: EMC Directive, Low Voltage Directive and Machinery Directive. C-Tick mark indicates compliance with the EMC requirements of Australia and New Zealand.
Safety	EN/IEC/UL 61010-1: Safety requirements for electrical equipment for measurement, control and laboratory use.
EMC Emission	EN/IEC 61000-6-3: Generic emission standard for residential, commercial and light industrial environments. CISPR 22: Radio disturbance characteristics of information technology equipment. Class B Limits. FCC Rules, Part 15: Complies with the limits for a Class B digital device.
EMC Immunity	EN/IEC 61000-6-1: Generic standards – Immunity for residential, commercial and light industrial environments. EN/IEC 61326: Electrical equipment for measurement, control and laboratory use – EMC requirements. Note: The above is only guaranteed using accessories listed in this Product Data Sheet.
Temperature	IEC 60068-2-1 & IEC 60068-2-2: Environmental Testing. Cold and Dry Heat. Operating Temperature: 5°C to 40°C (41°F to 104°F) Storage Temperature: -25°C to +70°C (-13°F to +158°F)
Humidity	IEC 60068-2-78: Damp Heat 0 to 90% RH (5°C to 40°C), non-condensing at 40°C
Enclosure	IEC 529: IP 20

Specifications – Turntable System Type 9640

Controllable Turntable Type 5960

Load: Max 100 kg (220 lb.) on centre, 30 kg (66 lb.) on periphery, when table plate is lined up perfectly in horizontal plane. Same loads apply with turntable hung upside down

Thread of Mounting Holes: UNF 10-32 and M5

Resolution: 1°

Speed of Rotation:

- **Cont. Mode:** 22.7 to 720 seconds per revolution
- **Turn_abs and Turn_rel Modes:** 10 seconds per revolution (max.)

Cable Length: 15 m (48.5 ft)

Table Plate Diameter: 354 mm (13.9")

Weight: 12 kg (26 lb.)

Turntable Controller Type 5997

OPERATING MODES

Turn_rel: Sets the relative turn in degrees

Turn_abs: Sets the absolute turn in degrees
Cont.: Sets the continuous speed in seconds per revolution

COMMANDS

Set 0 Deg: Sets the reference angle

Acc.: Sets the acceleration

Max_360 On/Off: Turns max. 360° on or off. On prevents cable wrapping

IEEE INTERFACE

Conforms with IEEE-488.1 and compatible with IEC 625-1. Provides remote control of all front-panel functions

FUNCTIONS IMPLEMENTED

- SH1 – Source Handshake
- AH1 – Acceptor Handshake
- L3 – Listener
- SR1 – Service Request
- DC1 – Device Clear
- RL1 – Remote/Local

COMMAND SET

Standard engineering English reflecting the front panel and screen names

Device Address: Set to 10 (decimal) on delivery

POWER SUPPLY

Voltage: 100, 115, 127, 200, 220 and 240 V
AC ±5%

Power Rating: approx. 15 VA

GENERAL

Cabinet: Supplied as model A (metal cabinet)

Dimensions:

Height: 143 mm (5.6")

Width: 188 mm (7.4")

Depth: 235 mm (9.3")

Weight: approximately 3 kg (6.6 lb.)

Ordering Information

Type 9640 Turntable System
Includes the following accessories:

Type 5960 Controllable Turntable

Type 5997 Turntable Controller

WB 1254 Remote Control

AO 0422 Turntable Cable

AN 0019 Power Cable (country specific)

AN 0020 Power Cable

2×JP 0101 Screened Plug

REQUIRED ACCESSORIES

AO 0265 Interface Cable (2 m), IEEE-488

WQ 1270 IEEE-488 Interface Card, PCI-GPIB

or

WQ 1290 IEEE-488 Interface Card, PCMCIA

Brüel & Kjær reserves the right to change specifications and accessories without notice

HEADQUARTERS: DK-2850 Nærum · Denmark · Telephone: +45 4580 0500 · Fax: +45 4580 1405
www.bksv.com · info@bksv.com

Australia (+61) 2 9889-8888 · Austria (+43) 1 865 74 00 · Brazil (+55) 11 5188-8161 · Canada (+1) 514 695-8225
China (+86) 10 680 29906 · Czech Republic (+420) 2 6702 1100 · Finland (+358) 9-521 300 · France (+33) 1 69 90 71 00
Germany (+49) 421 17 87 0 · Hong Kong (+852) 2548 7486 · Hungary (+36) 1 215 83 05 · Ireland (+353) 1 807 4083
Italy (+39) 0257 68061 · Japan (+81) 3 5715 1612 · Netherlands (+31) 318 55 9290 · Norway (+47) 66 77 11 55
Poland (+48) 22 816 75 56 · Portugal (+351) 21 41 69 040 · Republic of Korea (+82) 2 3473 0605
Singapore (+65) 6377 4512 · Slovak Republic (+421) 25 443 0701 · Spain (+34) 91 659 0820 · Sweden (+46) 8 449 8600
Switzerland (+41) 44 880 7035 · Taiwan (+886) 2 2502 7255 · United Kingdom (+44) 14 38 739 000
USA (+1) 800 332 2040 · Local representatives and service organisations worldwide

Brüel & Kjær 

