

# PRODUCT DATA

## ¼" DeltaTron<sup>®</sup> Pressure-field Microphones — Types 4944-A and 4944-B

Types 4944-A and 4944-B are ¼" Prepolarized Pressure-field Microphones laser welded to ¼" DeltaTron preamplifiers. The preamplifier connects to CCLD input conditioning and supports IEEE P 1451.4 V 0.9 TEDS (Transducer Electronic Data Sheet).

### USES

- High-level measurements
- High-frequency measurements
- Flush mounting
- Arrays in wind tunnels

### FEATURES

- Sensitivity: 0.9 mV/Pa
- Frequency: 16–70000 Hz
- Dynamic Range: 48 dB(A)–169 dB
- Temperature: –20 to +100°C (–4 to +212°F)
- TEDS: IEEE P1451.4



- SMB or 10–32 UNF socket
- Connects to CCLD input

### Description

#### Uses of Types 4944-A and 4944-B

A pressure-field microphone is designed to be used in small closed couplers, close to hard reflective surfaces or flush-mounted. The sensitivity has been optimised to allow measurements of high sound pressure levels without clipping in the built-in DeltaTron preamplifier.

#### Design and Robustness

The shape of the microphone front ensures excellent microphone performance when flush-mounted. The laser-welded diaphragm on the microphone housing ensures that the sensitivity is resistant to rough handling during flush mounting.


#### Microphone Data CD

The microphone is supplied with a mini-CD. This mini-CD carries all individual calibration data as well as random-incidence and free-field corrections. The influence of ¼" Nose Cone UA-0385 is also available.

#### Calibration

The sensitivity can be calibrated at 250 Hz using Pistonphone Type 4228 with ¼" Adaptor DP-0775. The pressure-field response can be measured using Actuator UA-0033 with Adaptor DB-0264. The pressure-field response is equal to the actuator response.

Fig. 1 Type 4944-A pressure-field response without grid



090119/1

## Specifications – Types 4944-A and 4944-B

Specification	Value <sup>†</sup>
<b>General Specifications</b>	
Nominal Diameter	¼"
Sensitivity (250 Hz)	-61 ±3 dB re 1 V/Pa, 0.9 mV/Pa
Frequency Response <sup>†</sup>	
Pressure-field Response	16 Hz to 70 kHz: ±2 dB
Lower Limiting Frequency	(-3 dB): 7 Hz to 9 Hz
Pressure Equalization Vent	Side vented
Diaphragm Resonance Frequency	60 kHz (90° phase-shift)
Equivalent Air Volume	0.25 mm <sup>3</sup> (250 Hz)
Thermal Noise	48 dB(A), 58 dB (Lin, 20 - 100 kHz) <sup>a</sup>
Upper Limit of Dynamic Range	> 169 dB SPL (3% Distortion)
Maximum Sound Pressure Level	182 dB (peak)
Power Requirements	DeltaTron Supply 2 to 20 mA, nom. 4 mA
DC Output Level	12 V ±2 V
Max. Output Voltage	7 V peak for $f \leq 70$ kHz (4 mA supply)
Output Impedance	<90 Ω, typ. 60 Ω
<b>Environmental</b>	
Operating Temperature Range	-20 to +100°C (-4 to +212°F)
Storage Temperature	
In case	-25 to +70°C (-13 to +158°F)
With data CD	5 to 50°C (41 to 122°F)
Temperature Coefficient (250 Hz)	+0.008 dB/°C (-10 to +50°C, 14 to 122°F)
Pressure Coefficient	-0.003 dB/kPa, typical
Operating Humidity Range	0 to 90% RH (without condensation)
Influence Of Humidity	<0.1 dB in the absence of condensation
Vibration Sensitivity (<1000 Hz)	69 dB equivalent SPL for 1 m/s <sup>2</sup>
Magnetic Field Sensitivity	<48 dB(A), 58 dB (Lin, 20 - 100 kHz for 80 A/m, 50 Hz field)
Estimated Long-term Stability	>1000 years/dB at 20°C (68°F) and dry air >40 years/dB at 20°C (68°F) and 90% RH >1 year/dB at 50°C (122°F) and 90% RH
<b>Physical</b>	
Diameter with Grid	7 mm (0.28")
Diameter without Grid	6.35 mm (0.25")
Length with Grid	65 mm (2.56")
Length without Grid	63.5 mm (2.50")
Output Socket	4944-A: SMB coaxial socket, male 4944-B: 10-32 UNF socket

<sup>a</sup> **Note:** All values are typical at 23°C (73.4°F), 101.3 kPa, 50% RH and ≥4 mA power supply, unless measurement uncertainty or tolerance field is specified. All uncertainty values are specified at 2σ (i.e., expanded uncertainty using a coverage factor of 2)

<sup>†</sup> Individually calibrated

## Ordering Information

Type 4944-A ¼" DeltaTron Pressure-field Microphone with SMB socket  
Type 4944-B ¼" DeltaTron Pressure-field Microphone with 10-32 UNF socket  
**Include the following accessories:**

- BC-5002: Microphone Data CD<sup>†</sup>

<b>Optional Accessories</b>	
Type 4231	Sound Calibrator
DP-0775	Calibration Adaptor for ¼" Microphones
DB-0264	½" to ¼" Adaptor for UA-0033
UA-0033	Electrostatic Actuator
UA-0385	Nose Cone for ¼" Microphones
UA-1588	¼" Microphone Holder
AO-0587-D-030	SMB-BNC Cable 3 m (10 ft.)
ZG-0328 (for Brüel & Kjær 7-pin sockets)	DeltaTron Power Supply
<b>Service Products</b>	
4944-CAF	Accredited Calibration
4944-CFF	Factory Standard Calibration (included with delivery)



Compliance with EMC Directive<sup>†</sup> and Low Voltage Directive of the EU

Compliance with the EMC requirements of Australia and New Zealand

<sup>\*</sup> Quote microphone serial number if re-ordering

<sup>†</sup> Without conducted RF noise

Brüel & Kjær reserves the right to change specifications and accessories without notice. © Brüel & Kjær. All rights reserved.

HEADQUARTERS: Brüel & Kjær Sound & Vibration Measurement A/S · DK-2850 Nærum · Denmark  
Telephone: +45 7741 2000 · Fax: +45 4580 1405 · www.bksv.com · info@bksv.com

Local representatives and service organisations worldwide

**Brüel & Kjær**

