

PRODUCT DATA

1/2" Pressure-field Microphone — Type 4192

Type 4192 is designed for high-precision coupler measurements or ANSI noise measurements. Being externally polarized, Type 4192 must be used with a classical preamplifier.



080146

USES

- Precision coupler measurement
- Premium class ANSI sound level meters
- General random incidence measurements

FEATURES

- Sensitivity: 12.5 mV/Pa
- Frequency: 3.15 Hz – 20 kHz
- Dynamic Range: 19 – 162 dB
- Temperature: –30 to +300°C (–22 to +572°F)
- Polarization: 200 V

Use of Pressure-field Microphones

Pressure-field microphones are optimised to have a flat frequency response in a pressure field. The microphones should be used for making measurements in small, closed couplers or close to hard, reflective surfaces.

Type 4192 is suited for situations where a robust and stable pressure-field microphone is required.

Manufacturing and Stability

A press-fitted, stainless-steel diaphragm ensures superior long-term stability and mechanical robustness – Type 4192 will withstand the 1 m drop test of IEC 60068–2–32.

All Brüel & Kjær Measuring Microphones are assembled in a clean room. This ensures that the microphones maintain their inherent low noise floor and high stability, even when used in environments with a combination of high humidity and high temperature.

Polarization Voltage

Type 4192 requires an external polarization voltage and must therefore must be used with a classical preamplifier. Externally polarized microphones may be used at higher temperatures without severe changes in sensitivity.

TEDS Microphones


Type 4192 is available in TEDS combinations with the classical Microphone Preamplifier Type 2669. The TEDS microphone is considered one unit and has been sealed in a clean environment. The TEDS is programmed with the loaded sensitivity of the actual cartridge and the data is therefore readily available. The default TEDS template is to IEEE P 1451.4 but TEDS to IEEE 1451.4 is available on request.

Individual Calibration Data

Each Type 4192 comes with an individual calibration chart with information about the open-circuit sensitivity and frequency response in a pressure field as well as the electrostatic actuator response.

An enclosed mini-CD contains the individual calibration data at 1/12-octave frequencies plus a wealth of technical information, such as the influence of different accessories, response in different sound fields and much more. Using the CD data and the REq-X feature of PULSE™, a real-time correction for different measurement situations, can increase measurement accuracy.

Fig. 1 Typical pressure field response of the microphone with protection grid. The low-frequency response is valid when the vent is exposed to the sound field



080118

Specifications – 1/2" Pressure-field Microphone Type 4192 (valid from serial number 2496392)

IEC 61094–4 Type Designation: WS2P

Polarization Voltage: 200 V (external)

Open-circuit Sensitivity (250 Hz)^a:

12.5 mV/Pa, –38 dB ± 1.5 dB re 1 V/Pa

Pressure-field Response^a:

5 Hz to 7 kHz: ± 1 dB

3.15 Hz to 20 kHz ± 2 dB

Lower Limiting Frequency (–3 dB)^a:

1 to 2 Hz

Pressure Equalization Vent: Side vented

Diaphragm Resonance Frequency:

23 kHz (90° phase shift)

Cartridge Capacitance (Polarized)^a:

18 pF at 250 Hz

Equivalent Air Volume: 8.8 mm³ (250 Hz)

Pistonphone Correction (Type 4228 with

DP-0776) 0.02 dB

Cartridge Thermal Noise:

19 dB(A), 21.3 dB(Lin)

Upper Limit of Dynamic Range

(3% Distortion): > 162 dB SPL^b

Max. Sound Pressure Level: 171 dB (peak)

ENVIRONMENTAL

Operating Temperature Range:

–30 to +150°C (–22 to +302°F)

Useable up to 300°C with a permanent sensitivity change of approx. 0.4 dB, which stabilizes after one hour.

Storage Temperature:

In Microphone Box: –30 to +70°C

(–22 to +158°F)

With Mini-CD: 5 to 50°C (41 to 122°F)

Temperature Coefficient (250 Hz):

–0.0045 dB/K (–10 to +50°C, 14 to 122°F)

Pressure Coefficient:

–0.005 dB/kPa, typical

Operating Humidity Range:

0 to 100% RH (without condensation)

Influence of Humidity:

< 0.1 dB in the absence of condensation

Vibration Sensitivity (< 1000 Hz): 65.5 dB equivalent SPL for 1 m/s² axial vibration

Magnetic Field Sensitivity:

16 dB SPL for 80 A/m, 50 Hz field

Estimated Long-term Stability:

> 1000 years/dB in dry air at 20°C (68°F)

> 100 hours/dB in dry air at 150°C (302°F)

DIMENSIONS

Diameter with Grid: 13.2 mm (0.52")

Diameter without Grid: 12.7 mm (0.50")


Height with Grid: 13.5 mm (0.53")

Height without Grid: 12.6 mm (0.50")

Thread for Preamp Mounting:

11.7 mm–60 UNS

Note: All values are typical at 23°C (73.4°F), 101.3 kPa and 50% RH unless otherwise specified



a. Individually calibrated

b. 149 dB (152 dB peak) with ± 15 V supply

Ordering Information

Type 4192 1/2" Pressure-field Microphone

Includes the following accessories:

- BC-0227: Calibration Chart^c
- BC-5002: Microphone Data CD^c

TEDS COMBINATIONS

4192-B-001 1/2" Pressure-field Microphone with Preamp Type 2669-B

4192-C-001 1/2" Pressure-field Microphone with Preamp Type 2669-C

4192-L-001 1/2" Pressure-field Microphone with Preamp Type 2669-L

OPTIONAL ACCESSORIES

Type 2669 1/2" Microphone Preamp

Type 4231 Sound Calibrator

Type 4228 Pistonphone

Type 4226 Multifunction Acoustic

Calibrator

DP-0776 Calibration Adaptor for 1/2" Microphones

UA-0033 Electrostatic Actuator

EU-4000 Angle Piece

UA-0386 Nose Cone for 1/2" Microphone

UA-0237 Windscreen for 1/2" Microphone, 90 mm diameter

UA-0459 Windscreen for 1/2" microphone, 65 mm diameter

BA 5105 The Microphone Handbook

CALIBRATION SERVICES

4192-CAI Accredited Initial Calibration

4192-CAF Accredited Calibration

4192-CFF Factory Standard Calibration

c. State microphone serial number if re-ordering calibration data

Brüel & Kjær reserves the right to change specifications and accessories without notice

HEADQUARTERS: DK-2850 Nærum · Denmark · Telephone: +45 4580 0500
Fax: +45 4580 1405 · www.bksv.com · info@bksv.com

Australia (+61) 2 9889-8888 · Austria (+43) 1 865 74 00 · Brazil (+55) 11 5188-8161
Canada (+1) 514 695-8225 · China (+86) 10 680 29906 · Czech Republic (+420) 2 6702 1100
Finland (+358) 9-755 950 · France (+33) 1 69 90 71 00 · Germany (+49) 421 17 87 0
Hong Kong (+852) 2548 7486 · Hungary (+36) 1 215 83 05 · Ireland (+353) 1 807 4083
Italy (+39) 0257 68061 · Japan (+81) 3 5715 1612 · Republic of Korea (+82) 2 3473 0605
Netherlands (+31) 318 55 9290 · Norway (+47) 66 77 11 55 · Poland (+48) 22 816 75 56
Portugal (+351) 21 4169 040 · Singapore (+65) 6377 4512 · Slovak Republic (+421) 25 443 0701
Spain (+34) 91 659 0820 · Sweden (+46) 33 225 622 · Switzerland (+41) 44 8807 035
Taiwan (+886) 2 2502 7255 · United Kingdom (+44) 14 38 739 000 · USA (+1) 800 332 2040

Local representatives and service organisations worldwide

Brüel & Kjær

